# TECH SPEC<sub>absolute</sub> separators





SEE WHAT PEERLESS CAN DO FOR YOU.

# FOR MAXIMUM SEPARATION EFFICIENCY OF SUB MICRON LIQUID DROPLETS IN CRITICAL SERVICES

**PEERLESS PERFORMANCE FEATURES** 

The Peerless Absolute Separator is a single or multi-stage device. At the inlet of the Primary Separation Section, small diameter cyclones or vanes remove liquid and solid particles by utilizing the dynamics of centrifugal force and gravity. By removing the bulk of the entrained liquid in this stage, the Peerless design increases the life of the High Efficiency Coalescing Elements and holds the pressure drop buildup to a minimum. This allows for more time between changing the elements, reducing operating costs and downtime.

Replacement of the coalescer elements can be accomplished in a minimum amount of time and effort through the use of a full diameter closure. Both cyclone or vane mist extractor separators are completely maintenance-free, self-cleaning and contain no replacement or moving parts to cause a shutdown.

## **TYPICAL APPLICATIONS:**

- Ammonia & urea plants
- DESICCANT BED PROTECTION
- CHEMICAL PLANTS
- OIL MIST REMOVAL
- CRITICAL GAS PROCESSES
- FUEL GAS CONDITIONING
- MOLECULAR SIEVE PROTECTION
- GAS TRANSMISSION/METERING
- POWER PLANTS



- INTRINSIC 2-STAGE CONFIGURATION
- FLEXIBLE PRIMARY STAGE SEPARATOR DESIGNS
- A VARIETY OF COALESCER MEDIA EFFICIENCIES
- GUARANTEED PERFORMANCE
- BUILT TO ASME CODE FOR INTERNATIONAL STANDARDS

## **CONSULT A PEERLESS SPECIALIST FOR YOUR** SEPARATION. RETROFIT AND SPARES REQUIREMENTS.



Peerless Cyclone Tube



Typical Peerless Vane Element



Absolute Separator



#### MAKING ENERGY SAFE. EFFICIENT. AND CLEAN.

**Corporate Headquarters** Peerless Mfg. Co. 14651 North Dallas Pkwy. Suite 500 Dallas, TX 75254 Phone 214-357-6181 www.peerlessmfg.com NASDAQ Symbol: PMFG

### **PRINCIPLE OF OPERATION**

**CYCLONE TUBE** 

As the mist- and solid-laden gas enters the Primary Separation Section of the vessel, the entrained liquids and sold particles are subjected to centrifugal force.

- (A) Dirty gas enters the Cyclone Tube tangentially at two locations.
- (B) The tube housing forces the gas into a cyclonic flow pattern. Centrifugal force throws solids and liquids against inner cyclone tube wall.
- (C) Solid and liquid particles drain down the cyclone tube walls and collect at bottom.
- (D) Clean gas flows down and then up through the center annulus and exits at the top.

#### VANE ELEMENT

In applications where solid particles are not a factor, vane mist extractors are used as the primary separator.

- (A) Contaminated gas entering the vane unit is directed into adjacent vertical channels where each one subjects the gas to rapid multiple changes in direction.
- (B) Inertial forces resulting from rapid direction change force liquid droplets against vane walls. Liquid droplets coalesce on the vane wall surface.
- (C) Gravity, surface tension, and momentum drive coalesced liquid into the vane pockets. Liquid flows down the pockets and collects in liquid reservoir.
- (D) Clean gas exits the tail end of the vane pack.

#### **COALESCING ELEMENT**

The final Separation Section consists of multiple High Efficiency Coalescing elements.

UNITED STATES New York office: 50 Cobham Dr Orchard Park NY 14127 Ph 716.662.6540

Houston office: 2930 W. Sam Houston Pkwy. Ste 225 Houston, TX 77043 Ph 281-655-7800

#### CANADA Peerless Manufacturing Canada

Ltd. 201-110 Country Hills Landing, NW Calgary, AB T3K5P3 Canada Ph 403-252-2600

EUROPE Peerless Europe Limited Cardinal's Court, Bradford St. Braintree, Essex CM7 9AT United Kingdom Ph +44-1376-556030

Burgess Manning Gmbh GoethestraBe 8 40237 Dusseldorf, Germany Ph +49 0211 690723-0

Asia Peerless Mfg. (Zhenjiang) Co. Ltd. 1-8 Ning Zhen Road Zhenjiang, Jiangsu China 212021 Ph +86 511-8572-8935

Peerless Asia Pacific Pte. Ltd. 35 Jalan Pemimpin, #07-02 Singapore 577176 Ph +65-6354-2306



THIS ABSOLUTE SEPARATOR IS INSTALLED ΙΝ Δ METERING STATION IN CANADA. ITS 99" ID HOUSING UTILIZES A FULL DIAMETER, QUICK-OPENING CLOSURE.

The gas and fine mists pass from the inside to the outside of the elements where the droplets diffuse and impinge on the closely spaced surfaces. The liquid then drains down the element and into the liquid collection chamber. Gas, free of liquid, exits through the outlet nozzle.

#### **PERFORMANCE GUARANTEE**

Peerless Absolute Separators meet separation efficiencies of 99.999% of droplets 0.3 to 0.6 microns in size with a maximum carryover of 0.001 PPM by mass depending on the coalescing media utilized.



A PEERLESS ABSOLUTE SEPARATOR CAN BE DESIGNED TO LIMIT LIQUID CARRYOVER TO LESS THAN 1PPB. HIGH **EFFICIENCY COALESCING ELEMENT SELECTION DEPENDS** YOUR SPECIFIC APPLICATION AND EFFICIENCY ON **REQUIREMENTS.**